

Schottky-based THz-MIC-s

Oleg Cojocari, Ion Oprea, Achim Walber, Hugh Gibson

<https://doi.org/10.1109/ICIMW.2008.4665549>

Abstract

This paper summarizes recently-achieved results for a frequency mixer and multiplier at Sub-mm-wavelengths, using a new-developed fabrication technology for Schottky-based Structures. Achieved results represent European state-of-the-art performance at these frequencies. Evaluation results suggest the suitability of the developed technology for applications at frequencies up to 1THz and beyond.

References

- 1.B. Thomas, H. Gibson, P. Hartogh, I. Medhi, A. Maestrini, E. Schlecht, M. Philipp,; Brandt, O. Cojocari, C. Lee, J. Gill, J. Siles, A. Walber, and S. Gulkis, "MMIC Schottky based receiver technology for the Submillimetre Wave Instrument - SWI-onboard EJSM/Laplace", Proceedings of 6 ESA Workshop on Millimetre-Wave Technology and Applications, 23 -25 May, Espoo(Finland), 2011.
- 2.Hugh J.E. Gibson, Achim Walber, Ralph Zimmermann, Byron Aldelman, Oleg Cojocari, "Improvements in Schottky harmonic Mixers for use up to 900GHz", Proceedings of 5 European Microwave Integrated Circuits Conference, Paris, 27-28 September, 2010.
- 3.Tero Kiuru, Juha Mallat, Antti V. Räisänen, and Tapani Narhi, «Schottky Diode Series Resistance and Thermal Resistance Extraction From S-Parameter and Temperature Controlled I-V Measurements», accepted for Publication in IEEE Trans. On Microwave Theory and Techniques in April 2011.